

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 1802A -moglice- 1000 FL 1802 resin
Print date: 03.07.2015 Revision date: 19.05.2015 65302 EN
Version: 2.0 Issue date: 19.05.2015 Page 1 / 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifiers

Article No. (manufacturer/supplier) 1802A
Identification of the substance or mixture -moglice- 1000 FL 1802 resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

DIAMANT Metallplastic GmbH
Hontzlarstr. 12-14 Telephone: +49(0)2166-98360
41238 Mönchengladbach Telefax: +49(0)2166-83025

Dept. responsible for information:

Lab
E-mail (competent person) info@diamant-polymer.de

1.4. Emergency telephone number

Emergency telephone number +49(0)2166-98360
Only available during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Sens. 1 / H317	respiratory or skin sensitisation	May cause an allergic skin reaction.
STOT RE 1 / H372	Specific target organ toxicity (repeated exposure)	Causes damage to organs through prolonged or repeated exposure.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.

Classification according to Directive 67/548/EEC or 1999/45/EC

This mixture is classified as hazardous according to 1999/45/EC.

Xi; R36/38	Irritant	Irritating to eyes and skin.
R43		May cause sensitization by skin contact.
Xn; R48/20/22	Harmful	Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.
R52-53		Harmful to aquatic life. May cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 1802A -moglice- 1000 FL 1802 resin
 Print date: 03.07.2015 Revision date: 19.05.2015 65302 EN
 Version: 2.0 Issue date: 19.05.2015 Page 2 / 8

P314 Get medical advice/attention if you feel unwell.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
 P337 + P313 If eye irritation persists: Get medical advice/attention.
 P501 Dispose of contents/container to industrial incineration plant.

contains:

Bisphenole A-epoxy resin
 Quartz
 N,N-Bis(2-3-epoxypropyl)aniline

Supplemental Hazard information (EU)

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Labelling (67/548/EEC or 1999/45/EC)



Xn Harmful

Hazard statements

36/38 Irritating to eyes and skin.
 43 May cause sensitization by skin contact.
 48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.
 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Precautionary statements

24 Avoid contact with skin.
 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 37 Wear suitable gloves.
 51 Use only in well-ventilated areas.
 61 Avoid release to the environment. Refer to special instructions/safety data sheet.

contains:

quartz
 reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)
 N,N-Bis(2-3-epoxypropyl)aniline

Special provisions concerning the labelling of certain mixtures

92 Contains epoxy constituents. May produce an allergic reaction.

2.3. **Other hazards**

SECTION 3: Composition / information on ingredients

*

3.2. **Mixtures**

Product description / chemical characterization

Description Epoxyresinmix + Fillers

Hazardous ingredients

Classification according to Regulation (EC) No. 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Chemical name classification	Wt % Remark
500-033-5 25068-38-6 603-074-00-8	01-2119456619-26 Bisphenole A-epoxy resin Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Aquatic Chronic 2 H411	10 - 25
238-878-4 14808-60-7	Quartz STOT RE 1 H372	10 - 25
218-259-5 2095-06-9	N,N-Bis(2-3-epoxypropyl)aniline Acute Tox. 4 H302 / Eye Irrit. 2 H319 / Skin Irrit. 2 H315 / Skin Sens. 1 H317	5 - 10
236-675-5 13463-67-7	Titandioxide Acute Tox. 5 H303 / Acute Tox. 5 H313 / Acute Tox. 5 H333	2,5 - 5

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 1802A -moglice- 1000 FL 1802 resin
Print date: 03.07.2015 Revision date: 19.05.2015 65302 EN
Version: 2.0 Issue date: 19.05.2015 Page 3 / 8

231-784-4	01-2119491274-35-0001	
7727-43-7	Bariumsulphate	1 - 2,5
231-159-6	01-2119480154-42	
7440-50-8	copper powder Flam. Sol. 1 H228 / Aquatic Acute 1 H400	< 0,5

Classification according to Directive 67/548/EEC or 1999/45/EC

EC No. CAS No. INDEX No.	REACH No. Chemical name classification	Wt % Remark
500-033-5	01-2119456619-26	
25068-38-6	reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average	10 - 25
603-074-00-8	molecular weight <= 700) Xi; R36/38 / R43 / N; R51-53	
238-878-4		
14808-60-7	quartz Xn; R48/20	10 - 25
218-259-5		
2095-06-9	N,N-Bis(2-3-epoxypropyl)aniline Xn; R22 / Xi; R36/37/38 / R43	5 - 10
231-784-4	01-2119491274-35-0001	
7727-43-7	Bariumsulphate	1 - 2,5 *
231-159-6	01-2119480154-42	
7440-50-8	Copper, Powder F; R11 / N; R50	< 0,5

Additional information

* Substance with a common (EC) occupational exposure limit value.

Full text of R-phrases: see section 16.

Full text of H-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 1802A
Print date: 03.07.2015
Version: 2.0

-moglice- 1000 FL 1802 resin
Revision date: 19.05.2015
Issue date: 19.05.2015

65302 EN
Page 4 / 8

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 20 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

INDEX No. not applicable / CAS No.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 1802A
Print date: 03.07.2015
Version: 2.0

-moglice- 1000 FL 1802 resin
Revision date: 19.05.2015
Issue date: 19.05.2015

65302 EN
Page 5 / 8

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Nitrile rubber or butyl rubber

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

*

9.1. Information on basic physical and chemical properties

Appearance:

Physical state liquid
Colour refer to label
Odour characteristic

Safety relevant basis data

	Unit	Method	Remark
Flash point:	135 °C	DIN 53213-1 (08/2002: replaced by EN ISO 1523)	
Ignition temperature in °C:	400 °C		
Lower explosion limit:	not applicable	Vol-%	
Upper explosion limit:	not applicable	Vol-%	
Vapour pressure at 20 °C:	not applicable	mbar	
Density at 20 °C:	1,94	g/cm ³	
Water solubility (g/L):	insoluble		
pH at 20 °C:	-		
Viscosity at °C:	Flüssig		
Solvent separation test (%):	< 3 %	ADR/RID	
Solid content (%):	99,88	Wt %	
solvent content:			
Organic solvents:	0	Wt %	
Water:	0	Wt %	

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 1802A -moglice- 1000 FL 1802 resin
Print date: 03.07.2015 Revision date: 19.05.2015
Version: 2.0 Issue date: 19.05.2015

65302 EN
Page 6 / 8

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

copper powder
oral, LD50, Rat:

Irritant and corrosive effects

Bisphenole A-epoxy resin
Skin (4 h)

Sensitisation

Bisphenole A-epoxy resin
Skin:

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

Toxicological data are not available.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this preparation do not meet the criteria for classification as CMR category 1 or 2 according to 67/548/EEC.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers. See chapters 2 and 15 for details.

SECTION 12: Ecological information

*

overall evaluation

There is no information available on the preparation itself .
Do not allow to enter into surface water or drains.

12.1. Toxicity

copper powder
Fish toxicity, LC50: (96 h)

Long-term Ecotoxicity

Bisphenole A-epoxy resin
Fish toxicity, LC50: (96 h)

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 1802A
Print date: 03.07.2015
Version: 2.0

-moglice- 1000 FL 1802 resin
Revision date: 19.05.2015
Issue date: 19.05.2015

65302 EN
Page 7 / 8

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111 waste paint and varnish containing organic solvents or other dangerous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

No dangerous good in sense of this transport regulation.

14.1. UN number

not applicable

14.2. UN proper shipping name

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Additional information

Land transport (ADR/RID)

tunnel restriction code

Sea transport (IMDG)

EmS-No. not applicable

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-value (in g/L) ISO 11890-2: 2

VOC-value (in g/L) ASTM D 2369: 2

National regulations

Restrictions of occupation

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 1802A
Print date: 03.07.2015
Version: 2.0

-moglice- 1000 FL 1802 resin
Revision date: 19.05.2015
Issue date: 19.05.2015

65302 EN
Page 8 / 8

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

Relevant R-and H-phrases (Number and full text):

Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Sens. 1 / H317	respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
STOT RE 1 / H372	Specific target organ toxicity (repeated exposure)	Causes damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Acute Tox. 5 / H303	Acute toxicity (oral)	May be harmful if swallowed.
Acute Tox. 5 / H313	Acute toxicity (dermal)	May be harmful in contact with skin.
Acute Tox. 5 / H333	Acute toxicity (inhalative)	May be harmful if inhaled.
Flam. Sol. 1 / H228	Flammable solids	Flammable solid.
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic life.
Xi; R36/38	Irritant	Irritating to eyes and skin.
R43		May cause sensitization by skin contact.
N; R51-53	Dangerous for the environment	Toxic to aquatic life. May cause long-term adverse effects in the aquatic environment.
Xn; R48/20	Harmful	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
F; R11	Highly flammable	Highly flammable
N; R50	Dangerous for the environment	Very toxic to aquatic life.
Xn; R22	Harmful	Harmful if swallowed.
Xi; R36/37/38	Irritant	Irritating to eyes, respiratory system and skin.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Additional information

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version