

Article Print c		1130A 22.07.2015	-moglice- P 1130 resin Revision date: 14.07.2015	65302 EN
Versic		2.1	Issue date: 14.07.2015	Page 1 / 8
	SECTION	1: Identification	n of the substance/mixture and	of the company/undertaking
1.1.	Product id			
		(manufacturer/sup on of the substance		130 resin
1.2.	Relevant i	dentified uses of	the substance or mixture and uses	
1.3.			e safety data sheet	
	••••	nanufacturer/imp Metallplastic Gmbł	orter/downstream user/distributor) ⊣	
	Hontzlarstr	. 12-14	Telephone: +	49(0)2166-98360
		ichengladbach onsible for inforn		0)2166-83025
	Lab			
1.4.	-	npetent person) y telephone numl	info@diamar	t-polymer.de
1.4.		telephone numbe		98360
	Only availa	ble during office h	ours.	
	SECTION	2: Hazards ide	ntification	
2.1.		ion of the substa		
		-	Regulation (EC) No. 1272/2008 [CL azardous according to regulation (EC	-
	Skin Irrit. 2		skin corrosion/irritation	Causes skin irritation.
	Eye Irrit. 2		Serious eye damage/eye irritation	Causes serious eye irritation.
	Skin Sens. STOT RE 1		respiratory or skin sensitisation Specific target organ toxicity (repe	May cause an allergic skin reaction. Causes damage to organs through prolonged
	Aquatic Ch	ronic 3 / H412	exposure) Hazardous to the aquatic environn	or repeated exposure. Harmful to aquatic life with long lasting effects.
	-		Directive 67/548/EEC or 1999/45/E0	
	This mixtur	e is classified as h	azardous according to 1999/45/EC.	
	Xi; R36/38		Irritant	Irritating to eyes and skin.
	R43 R52-53			May cause sensitization by skin contact. Harmful to aquatic life. May cause long-term adverse effects in the aquatic environment.
2.2.	Label elem			
	Labelling a Hazard pic		ulation (EC) No. 1272/2008 [CLP]	
	$\langle \cdot \rangle$		Danger	
	Hazard sta	itements		
	H315		s skin irritation.	
	H319 H317		s serious eye irritation. ause an allergic skin reaction.	
	H372		s damage to organs through prolonge	ed or repeated exposure.
	H412	Harmfu	ul to aquatic life with long lasting effe	
	Precaution P261	nary statements Avoid	breathing dust/fume/gas/mist/vapours	s/spray.
	P273		release to the environment.	» ~p· ~ J ·
	P280		protective gloves/protective clothing/e	
	P302 + P35 P305 + P35	51 + P338 IF IN E		water. several minutes. Remove contact lenses, if present and
	P314		o do. Continue rinsing. edical advice/attention if you feel unw	ell
	1 0 1 4	Gerlin		
	P333 + P37		irritation or rash occurs: Get medical	



				The Metalplastic Company	
Article Print c Versic	late:	1130A 22.07.2015 2.1	-moglice- P 1130 resin Revision date: 14.07.2015 Issue date: 14.07.2015	65302 EN Page 2 / 8	
	P501	Dispo	se of contents/container to industrial in	cineration plant.	
	contains:				
			enole A-epoxy resin		
			(quartz) glass		
			is(2-3-epoxypropyl)aniline		
		ntal Hazard infor			
	EUH205		ins epoxy constituents. May produce a	n allergic reaction.	
	Labelling	67/548/EEC or 1	999/45/EC)		
	×	Xi Irr	tant		
	Hazard sta	tements			
	36/38	Irritati	ng to eyes and skin.		
	43 May cause sensitization by skin contact.				
	52/53	Harm	ul to aquatic organisms, may cause lo	ng-term adverse effects in the aquatic environment.	
	Precaution	nary statements			
	24		contact with skin.		
	26		•	ly with plenty of water and seek medical advice.	
	37 61		suitable gloves. release to the environment. Refer to s	pacial instructions/safaty data shoat	
	-	Avoiu	release to the environment. Relef to s		
	contains:		on product: bisphenol A-(epichlorhydrir is(2-3-epoxypropyl)aniline); epoxy resin (number average molecular weight <= 700	
	Special pr	ovisions concer	ning the labelling of certain mixtures		
	92		ins epoxy constituents. May produce a		
2.3.	Other haza	ards			
	SECTION	3: Compositio	n / information on ingredients		
3.2.	Mixtures				
	Product de	escription / chem	nical characterization		
	Descriptio	n Epoxy	vresinmix + Fillers		
	-	s ingredients			
	Classificat	tion according to	Regulation (EC) No. 1272/2008 [CLF	1	

Classification ac	cording to Regulation (EC) No. 1272/2008 [CLP]	
EC No.	REACH No.	
CAS No.	Chemical name	Wt %
INDEX No.	classification	Remark
500-033-5	01-2119456619-26	
25068-38-6	Bisphenole A-epoxy resin	10 - 25
603-074-00-8	Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Aquatic Chronic 2 H411	
262-373-8		
60676-86-0	Silica (quartz) glass STOT RE 1 H372	10 - 25
218-259-5		
2095-06-9	N,N-Bis(2-3-epoxypropyl)aniline	2,5 - 5
	Acute Tox. 4 H302 / Eye Irrit. 2 H319 / Skin Irrit. 2 H315 / Skin Sens. 1 H317	
Classification ac	cording to Directive 67/548/EEC or 1999/45/EC	
EC No.	REACH No.	
CAS No.	Chemical name	Wt %
INDEX No.	classification	Remark
500-033-5	01-2119456619-26	
25068-38-6	reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average	10 - 25
603-074-00-8	molecular weight <= 700)	
	Xi; R36/38 / R43 / N; R51-53	
218-259-5		
2095-06-9	N,N-Bis(2-3-epoxypropyl)aniline	2,5 - 5
	Xn; R22 / Xi; R36/37/38 / R43	



Article No.:	1130A	-moglice- P 1130 resin
Print date:	22.07.2015	Revision date: 14.07.2015
Version:	2.1	Issue date: 14.07.2015

65302 EN Page 3 / 8

Additional information

Full text of R-phrases: see section 16. Full text of H-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only



Article No.:	1130A	-moglice- P 1130 resin	
Print date:	22.07.2015	Revision date: 14.07.2015	65302 EN
Version:	2.1	Issue date: 14.07.2015	Page 4 / 8

use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 20 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

INDEX No. not applicable / CAS No.

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Nitrile rubber or butyl rubber

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties



Article No.: Print date: Version:	1130A 22.07.2015 2.1	-moglice- P 1130 resin Revision date: 14.07.2015 Issue date: 14.07.2015	65302 EN Page 5 / 8	
---	----------------------------	---	------------------------	--

9.1. Information on basic physical and chemical properties

Appearance:				
Physical state	liquid			
Colour	refer to label			
Odour	characteristic			
Safety relevant basis data		Unit	Method	Remark
Flash point:	135	°C	DIN 53213-1 (08/2002: replaced by EN ISO 1523)	
Ignition temperature in °C:	520	°C		
Lower explosion limit:	not applicable	Vol-%		
Upper explosion limit:	not applicable	Vol-%		
Vapour pressure at 20 °C:	not applicable			
Density at 20 °C:	2,18	g/cm³		
Water solubility (g/L):	insoluble	•		
pH at 20 °C:	-			
Viscosity at °C:	Pastös			
Solvent separation test (%):	< 3	%	ADR/RID	
Solid content (%):	99,84	Wt %		
solvent content:	_			
Organic solvents:		Wt %		
Water:	0	Wt %		
Other information				

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

Toxicological data are not available.

Irritant and corrosive effects

Bisphenole A-epoxy resin Skin (4 h)

Sensitisation

Bisphenole A-epoxy resin Skin:

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

Toxicological data are not available.

Practical experience/human evidence



Article No.:	1130A	-moglice- P 1130 resin	
Print date:	22.07.2015	Revision date: 14.07.2015	65302 EN
Version:	2.1	Issue date: 14.07.2015	Page 6 / 8

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this preparation do not meet the criteria for classification as CMR category 1 or 2 according to 67/548/EEC.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers. See chapters 2 and 15 for details.

SECTION 12: Ecological information

overall evaluation

There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

12.1. Toxicity

Toxicological data are not available.

Long-term Ecotoxicity

Bisphenole A-epoxy resin Fish toxicity, LC50: (96 h)

- 12.2. Persistence and degradability Toxicological data are not available.
- 12.3. Bioaccumulative potential

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111 waste paint and varnish containing organic solvents or

other dangerous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

No dangerous good in sense of this transport regulation.

14.1. UN number

not applicable

14.2. UN proper shipping name

14.3. Transport hazard class(es)

not applicable



Article No.: Print date: /ersion:	1130A 22.07.2015 2.1	-moglice- P 1130 resin Revision date: 14.07.2015 Issue date: 14.07.2015	65302 EN Page 7 / 8
14.4. Packing	group		
		not applicable	
14.5. Environ	mental hazards		
Land trai	nsport (ADR/RID)	not applicable	
Marine p	ollutant	not applicable	
14.6. Special	precautions for use	r	
case of a	rt always in closed, u an accident or leakag on safe handling: see	je.	hat persons transporting the product know what to do in
Additior	nal information		
Land tra	insport (ADR/RID)		
tunnel re	striction code		
Sea tran	sport (IMDG)		
EmS-No		not applicable	
14.7. Transpo	ort in bulk according	g to Annex II of MARPOL 73/78 and th	e IBC Code
not appli	cable		
SECTIC	ON 15: Regulatory	information	
15.1. Safety, I	health and environn	nental regulations/legislation specific	for the substance or mixture
EU legis			
VOC-val	tion according to 19 ue (in g/L) ISO 1189 ue (in g/L) ASTM D 2	0-2: 3	ns of volatile organic compounds (VOC-guideline).
	l regulations		
Restrict Observe	ions of occupation employment restriction		ctive (92/85/EEC) for expectant or nursing mothers. enile work protection guideline' (94/33/EC).
Other re	gulations, restriction	ons and prohibition regulations	
	al Safety Assessme	nt s for substances in this preparation were	e not carried out.
SECTIC	N 16: Other infor	mation	
Relevan	t R-and H-phrases (Number and full text):	
	. 2 / H315	skin corrosion/irritation	Causes skin irritation.
•	2/H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Aquatic (ns. 1 / H317 Chronic 2 / H411 E 1 / H372	respiratory or skin sensitisation Hazardous to the aquatic environmer Specific target organ toxicity (repeate exposure)	
Acute To Xi; R36/3 R43 N; R51-5		Acute toxicity (oral) Irritant Dangerous for the environment	is conclusively proven that no other routes of exposure cause the hazard). Harmful if swallowed. Irritating to eyes and skin. May cause sensitization by skin contact. Toxic to aquatic life. May cause long-term
Xn; R22 Xi; R36/3		Harmful Irritant	adverse effects in the aquatic environment. Harmful if swallowed. Irritating to eyes, respiratory system and skin.
	ations and acronym		initialing to eyes, respiratory system and shift.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Additional information

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and



Article No.:	1130A	-moglice- P 1130 resin	
Print date:	22.07.2015	Revision date: 14.07.2015	
Version:	2.1	Issue date: 14.07.2015	

EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

65302 EN Page 8 / 8